

Technology | Document Management | Consulting Services

fax print copy scan

A power-packed office tool

Be productive.

A robust fax machine at its core, the FaxCentre® 2218 is all about productivity. Powerful enough to handle the most demanding fax workload, you get more standard features, unbeatable performance, and the added convenience of printing, copying and color scanning.





	FaxCentre® 2218
Speed	Up to 18 ppm (letter) / 17 ppm (A4)
Duty Cycle	20,000 pages / month
Paper Handling Paper input	Bypass Tray: 100 sheets; Selectable sizes: Letter, Legal, Folio, Executive, A4, B5, A5 Tray 1: 550 sheets; Selectable sizes: Letter, Legal, Folio, A4
Optional	Tray 2: 550 sheets; Selectable sizes: Letter, Legal, Folio, A4
Document handler	Duplex Automatic Document Feeder: 50 sheets; Custom sizes: 5.7×5.8 in. to 8.5×14 in. / 145×148 mm to 216×356 mm
Paper output	250 sheets
Two-sided output	Standard
Fax	Walkup Fax (33.6 Kbps with JBIG Compression), PC Fax
Optional	LAN Fax
Speed	As fast as 3 seconds per page
Resolution (max)	Up to 406 x 392 dpi black-and-white / 300 x 300 dpi color
Fax features	Toll save, Memory fax, Delay fax, Priority fax, Polling, Batch TX, Secure fax receive, Charge codes, Mailboxes, Speed dials, One touch dials
Print First-page-out time	As fast as 12 seconds
Resolution (max)	600 x 600 dpi, 1200 x 600 dpi
Language support	PCL® 5e emulation, PCL 6 emulation
Optional	PostScript® 3™ compatibility
Connectivity	USB 2.0, Parallel
Optional	10/100Base-TX Ethernet
Print features	Automatic two-sided, Poster and Booklet printing, Fit to page, Reduce/Enlarge, Cover sheets, Collation, Watermarks
Copy First-page-out time	As fast as 10 seconds
Resolution (max)	600 x 600 dpi
Copy features	Collation, ID Card Copy, Edge erase, Margin shift, Book Copying, Background suppression, Covers, Transparencies, Booklet creation, N-up, Clone, Auto fit
Scan	Scan to desktop, bundled OCR software (Nuance PaperPort®, OmniPage®), Color Scanning
Other Options	Network kit, Foreign device interface kit, Cabinet stand

Device Management

ControlCentre® 5.0, CentreWare® IS Embedded Web Server, CentreWare Web, NDPS Gateway, CentreWare for HP® OpenView®, Unicenter TNG, Tivoli NetView

General Specifications

System memory: 64 MB Fax memory: 16 MB (stores up to 1,280 pages)* Total memory: 80 MB

Compression: JBIG/G3/Super Group 3/ MMR/MR/MH/JPEG Halftones: 256 levels 100 mailboxes, 100 department codes Dialing: Up to 400 Speed / 399 Group dials, 60 One touch dials Battery backup: Up to 100 hours

Print Drivers

Windows 98/Me/NT 4.0/ 2000/XP, Mac OS® 10.2, 10.4, Linux®

Scan resolution: 600 x 600 dpi optical, 4800 enhanced dpi QuickScan speed: 1.6 seconds per page at 203 x 98 dpi Scan driver: WIA, TWAIN

Media Handling

labels, cardstock

Bypass tray: 16 to 43 lb. bond / 60 to 163 gsm Tray 1 (standard) and Tray 2 (optional): 16 to 24 lb. bond / 60 to 90 gsm Two-sided output: 20 to 24 lb. bond / 80 to 90 gsm Media types: paper, transparencies,

Operating Environment

Temperature: 50° to 90°F / 10° to 32°C Humidity: 20 to 80% Sound power levels: Operating: 66 dB, Standby: 48 dB

Electrical

Power: 110 - 127 V, 50/60 Hz Power consumption: Operation: Avg 450 W Power Save Mode: 28 W **ENERGY STAR® compliant**

Dimensions (WxDxH) 22 x 16.9 x 19.5 in. / 560 x 430 x 495 mm Weight: 56.5 lb. / 25.7 kg

Certifications UL Safety / cUL

Supplies

Toner – Black: 8,000 pages¹ 006R01278 (ships with 4,000-page cartridge) Drum cartridge: 20,000 pages2 113R00671













- Average standard pages. Declared Yield in accordance with ISO/IEC 19752. Yield will vary based on image, area coverage and print mode.
- Approximate pages. Yield will vary depending on job run length and media size and orientation

© 2007 Xerox Corporation. All rights reserved. XEROX® and FaxCentre® are trademarks of Xerox Corporation. In support of Xerox Corporation's environmental leadership goals, these models may contain some recycled components that are reconditioned. PaperPort® and OmmiPage® are registered trademarks of Nuance Communications, Incorporated. ENERGY STAR® and the ENERGY STAR® mark are registered U.S. marks. As an ENERGY STAR® Partner, Xerox has determined that these products meet the ENERGY STAR® guidelines for energy efficiency, PCL® is a registered trademark of Hewlett-Packard Co. PostScript® and PostScript® 3" are either registered trademarks or trad

Call today. For more information, call **1-877-362-6567** or visit us at www.xerox.com/office

Uncompromised power makes the FaxCentre® 2218 a high-end fax workhorse that's truly convenient.

High-volume fax performance

- The robust engine can handle the most demanding workloads with a duty cycle of up to 20,000 images per month.
- 33.6 Kbps modem transmits multipage documents in as little as 3 seconds per page.
- Spend less time waiting with a speedy 18 ppm print engine.
- 16 MB of fax memory stores up to 1,280 pages*.
- The 50-sheet duplex automatic document feeder allows you to process and send large, doublesided fax jobs.

Advanced fax features

- PC Fax allows convenient, paperless faxing right from your desk.
- Intuitive user interface lets you fax at the touch of a button.
- Password protected mailboxes receive and protect sensitive documents.
- · Convenient fax forward to fax capability lets you quickly archive or share faxes.

Do-it-all versatility

- Fax smaller-size documents such as receipts directly from the platen glass — no need to make copies beforehand.
- Standard 650-sheet paper capacity can be increased to 1200 sheets for added convenience and less-frequent paper loading.
- Standard 4-in-1 multifunctionality saves you space and money by consolidating standalone devices.
- Optional network connectivity kit enables network printing, LAN Fax, Mac OS, Linux and PostScript 3 emulation for exceptional print quality.
- Nuance PaperPort® and OmniPage® scanning software helps digitize and organize documents.